

# FLOORS TORONTO

EUROPEAN WHITE OAK COLLECTION

Product # FT-SP-75

SKU Straight Plank 7 1/2 in

Website floorstoronto.ca

## Straight Plank 7 1/2 in

Classic linear plank for residential and commercial rooms.

Straight Plank

3/4" x 7 1/2" W x 3.1'-6.2' L

Grade: AB and ABC

### CONSTRUCTION AND DIMENSIONS

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Wood species    | European White Oak                                    |
| Construction    | Engineered hardwood, multi-layer cross-ply birch core |
| Total thickness | 3/4" (19 mm)                                          |
| Veneer layer    | 4 mm European white oak                               |
| Size            | 3/4" x 7 1/2" W x 3.1'-6.2' L                         |
| Format          | Straight Plank                                        |
| Grade           | AB and ABC                                            |
| Joint type      | Tongue and groove                                     |

### CHARACTERISTICS

|                          |                                           |
|--------------------------|-------------------------------------------|
| Surface finish           | UV-cured aluminum oxide, satin            |
| Finish coats             | 7 UV-cured layers                         |
| Janka hardness           | 1290 lbf (White Oak)                      |
| Radiant heat compatible  | Yes                                       |
| Below-grade installation | Yes                                       |
| Installation methods     | Nail, Glue, Float                         |
| Subfloor compatibility   | Wood, Concrete, Existing tile             |
| Custom stain service     | Free colour match included on every order |

### INSTALLATION, STORAGE AND USAGE

Install over approved wood or concrete subfloors using project-specified adhesive or fastening method. Maintain indoor air humidity between 40% and 65% and temperature between 18 C and 22 C. Specifications subject to confirmation prior to production.

# FLOORS TORONTO

EUROPEAN WHITE OAK COLLECTION

**Product #** FT-SP-925

**SKU** Straight Plank 9 1/4 in

**Website** floorstoronto.ca

## Straight Plank 9 1/4 in

Wide plank format with balanced scale and clean lines.

Straight Plank

3/4" x 9 1/4" W x 3.1'-6.2' L

Grade: AB and ABC

### CONSTRUCTION AND DIMENSIONS

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Wood species    | European White Oak                                    |
| Construction    | Engineered hardwood, multi-layer cross-ply birch core |
| Total thickness | 3/4" (19 mm)                                          |
| Veneer layer    | 4 mm European white oak                               |
| Size            | 3/4" x 9 1/4" W x 3.1'-6.2' L                         |
| Format          | Straight Plank                                        |
| Grade           | AB and ABC                                            |
| Joint type      | Tongue and groove                                     |

### CHARACTERISTICS

|                          |                                           |
|--------------------------|-------------------------------------------|
| Surface finish           | UV-cured aluminum oxide, satin            |
| Finish coats             | 7 UV-cured layers                         |
| Janka hardness           | 1290 lbf (White Oak)                      |
| Radiant heat compatible  | Yes                                       |
| Below-grade installation | Yes                                       |
| Installation methods     | Nail, Glue, Float                         |
| Subfloor compatibility   | Wood, Concrete, Existing tile             |
| Custom stain service     | Free colour match included on every order |

### INSTALLATION, STORAGE AND USAGE

Install over approved wood or concrete subfloors using project-specified adhesive or fastening method. Maintain indoor air humidity between 40% and 65% and temperature between 18 C and 22 C. Specifications subject to confirmation prior to production.

# FLOORS TORONTO

EUROPEAN WHITE OAK COLLECTION

Product # FT-SP-1025

SKU Straight Plank 10 1/4 in

Website floorstoronto.ca

## Straight Plank 10 1/4 in

Widest plank option for larger open-plan layouts.

Straight Plank

3/4" x 10 1/4" W x 3.1'-7.2' L

Grade: AB and ABC

### CONSTRUCTION AND DIMENSIONS

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Wood species    | European White Oak                                    |
| Construction    | Engineered hardwood, multi-layer cross-ply birch core |
| Total thickness | 3/4" (19 mm)                                          |
| Veneer layer    | 4 mm European white oak                               |
| Size            | 3/4" x 10 1/4" W x 3.1'-7.2' L                        |
| Format          | Straight Plank                                        |
| Grade           | AB and ABC                                            |
| Joint type      | Tongue and groove                                     |

### CHARACTERISTICS

|                          |                                           |
|--------------------------|-------------------------------------------|
| Surface finish           | UV-cured aluminum oxide, satin            |
| Finish coats             | 7 UV-cured layers                         |
| Janka hardness           | 1290 lbf (White Oak)                      |
| Radiant heat compatible  | Yes                                       |
| Below-grade installation | Yes                                       |
| Installation methods     | Nail, Glue, Float                         |
| Subfloor compatibility   | Wood, Concrete, Existing tile             |
| Custom stain service     | Free colour match included on every order |

### INSTALLATION, STORAGE AND USAGE

Install over approved wood or concrete subfloors using project-specified adhesive or fastening method. Maintain indoor air humidity between 40% and 65% and temperature between 18 C and 22 C. Specifications subject to confirmation prior to production.

# FLOORS TORONTO

EUROPEAN WHITE OAK COLLECTION

**Product #** FT-HB-50  
**SKU** Herringbone 5 in  
**Website** floorstoronto.ca

## Herringbone 5 in

Classic geometric pattern for luxury and heritage interiors.

Herringbone

3/4" x 5" W x 25" L

Grade: AB

### CONSTRUCTION AND DIMENSIONS

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Wood species    | European White Oak                                    |
| Construction    | Engineered hardwood, multi-layer cross-ply birch core |
| Total thickness | 3/4" (19 mm)                                          |
| Veneer layer    | 4 mm European white oak                               |
| Size            | 3/4" x 5" W x 25" L                                   |
| Format          | Herringbone                                           |
| Grade           | AB                                                    |
| Joint type      | Tongue and groove                                     |

### CHARACTERISTICS

|                          |                                           |
|--------------------------|-------------------------------------------|
| Surface finish           | UV-cured aluminum oxide, satin            |
| Finish coats             | 7 UV-cured layers                         |
| Janka hardness           | 1290 lbf (White Oak)                      |
| Radiant heat compatible  | Yes                                       |
| Below-grade installation | Yes                                       |
| Installation methods     | Nail, Glue, Float                         |
| Subfloor compatibility   | Wood, Concrete, Existing tile             |
| Custom stain service     | Free colour match included on every order |

### INSTALLATION, STORAGE AND USAGE

Install over approved wood or concrete subfloors using project-specified adhesive or fastening method. Maintain indoor air humidity between 40% and 65% and temperature between 18 C and 22 C. Specifications subject to confirmation prior to production.

# FLOORS TORONTO

EUROPEAN WHITE OAK COLLECTION

**Product #** FT-CH-50

**SKU** Chevron 5 in

**Website** floorstoronto.ca

## Chevron 5 in

Directional V-pattern for modern statement installations.

Chevron

3/4" x 5" W x 25 1/2" L

Grade: AB

### CONSTRUCTION AND DIMENSIONS

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Wood species    | European White Oak                                    |
| Construction    | Engineered hardwood, multi-layer cross-ply birch core |
| Total thickness | 3/4" (19 mm)                                          |
| Veneer layer    | 4 mm European white oak                               |
| Size            | 3/4" x 5" W x 25 1/2" L                               |
| Format          | Chevron                                               |
| Grade           | AB                                                    |
| Joint type      | Tongue and groove                                     |

### CHARACTERISTICS

|                          |                                           |
|--------------------------|-------------------------------------------|
| Surface finish           | UV-cured aluminum oxide, satin            |
| Finish coats             | 7 UV-cured layers                         |
| Janka hardness           | 1290 lbf (White Oak)                      |
| Radiant heat compatible  | Yes                                       |
| Below-grade installation | Yes                                       |
| Installation methods     | Nail, Glue, Float                         |
| Subfloor compatibility   | Wood, Concrete, Existing tile             |
| Custom stain service     | Free colour match included on every order |

### INSTALLATION, STORAGE AND USAGE

Install over approved wood or concrete subfloors using project-specified adhesive or fastening method. Maintain indoor air humidity between 40% and 65% and temperature between 18 C and 22 C. Specifications subject to confirmation prior to production.